




# Fiberglass Reinforced Polymer Panels

285 Industrial Drive  
 Moscow, TN 38057  
 Ph: 888-737-6548  
 Fax: 901-877-1388  
 Email: sales@resolite.com

## Technical Data



## 2-1/2 X 1/2" Load/Span Tables (STANDARD PROFILE)

- 1 denotes simple span condition
- 2 denotes double span condition
- 3 denotes triple span condition

### SIDING/ROOFING WIND LOADS (PSF)

	20			30			40			50			60		
	1	2	3	1	2	3	1	2	3	1	2	3	1	2	3
Tred-Safe															
1240															
1040															
840															
1230	3' 7"	4' 10"	4' 5"	3' 2"	4' 2"	3' 10"	2' 10"	3' 10"	3' 6"	2' 8"	3' 6"	3' 3"	2' 6"	3' 4"	3' 1"
1030	3' 4"	4' 6"	4' 2"	2' 11"	3' 11"	3' 8"	2' 8"	3' 7"	3' 4"	2' 6"	3' 4"	3' 1"	2' 4"	3' 2"	2' 11"
830	3' 2"	4' 2"	3' 10"	2' 9"	3' 8"	3' 4"	2' 6"	3' 4"	3' 1"	2' 4"	3' 1"	2' 10"	2' 2"	2' 11"	2' 8"
RFM 17															
RFM 14															
RFM 11															

### ROOFING LIVE LOADS (PSF)

	20			30			40			50			60		
	1	2	3	1	2	3	1	2	3	1	2	3	1	2	3
Tred-Safe															
1240															
1040															
840															
1230	2' 9"	3' 8"	3' 4"	2' 5"	3' 2"	2' 11"	2' 2"	2' 11"	2' 8"	2' 0"	2' 8"	2' 6"	1' 11"	2' 6"	2' 4"
1030	2' 7"	3' 5"	3' 2"	2' 3"	3' 0"	2' 9"	2' 0"	2' 9"	2' 6"	1' 11"	2' 6"	2' 4"	1' 9"	2' 5"	2' 2"
830	2' 5"	3' 2"	2' 11"	2' 1"	2' 10"	2' 7"	1' 11"	2' 6"	2' 4"	1' 9"	2' 4"	2' 2"	1' 8"	2' 3"	2' 1"
RFM 17															
RFM 14															
RFM 11															

- NOTES:**
1. Load/Span limits are based on full scale panel tests representing actual field conditions.
  2. Panel span/deflection ratios (L/D) shall be limited to L/20 for wind loads and L/45 for live loads.
  3. Factors of safety shall be 1.88 for panels subjected to wind loads and 2.5 for panels subjected to live loads.
  4. Load/Span limits are based on fasteners with 5/8" washers in every other high.
  5. Other panel types, weights, glass reinforcements, resin types, lengths, fastening options, or special loading requirements may be available; please contact Resolite Customer Service Department for more information.
  6. All roof slopes are a minimum of 1:12. For slopes less than 1:12, contact Resolite Customer Service Dept.

### DIMENSIONS

**Standard**  
 Finish Width ..... 51.5"  
 Coverage Width ..... 48"  
 Lengths ..... 4' to 30'

**Optional**  
 Finish Width ..... 50"  
 Coverage Width ..... 48"

### PANEL TYPES NOMINAL WEIGHT (OZ./SQ.FT.)

- 1645 Tred-Safe...not available
- 1240 thru 840 .... not available
- 1230 ..... 12
- thru ..... thru
- 830 ..... 8
- RFM 17 .....not available
- RFM 14 .....not available
- RFM 11 .....not available

### ADDITIONAL INFORMATION

Consult Table of Contents for specific information regarding:

- FRP Panel Design
- Fire Resistance & Codes
- Corrosion & Weathering
- Color, Finish, & Light Transmission
- Fasteners & Accessories
- Product Descriptions
- FRP Panel Specifications
- Profile Selection Guide
- Flashing Details
- Installation, Storage, & Handling
- FRP Louvers, Ventilators, Gutters & Downspouts